



ORBIFEED EXTERNAL WIRE FEED UNITS

Compact and lightweight wire feed unit mounted in a Peli case for 5kg (ORBIFEED 5) and 15kg (ORBIFEED 15) standard spools.

EXTERNAL WIRE FEED UNIT ORBIFEED 5, for 5kg – spools

1.3.1701

EXTERNAL WIRE FEED UNIT ORBIFEED 15, for 15kg – spools

1.3.1702

Technical Data:

	Orbifeed 5	Orbifeed 15
Motor voltage and power	24V DC, 6W	24V DC, 6W
Weight	approx. 7kg	approx. 8kg
Dimensions (L x W x H)	406 x 330 x 174mm	525 x 436 x 217mm
Wire spools	Standard spools 5kg	Standard spools 5 and 15kg
Wire outside diameter	0.8 / 1.0mm	0.8 / 1.0mm

Package includes:

- Water-resistant and dust-proof Peli case
- Four roller drive mechanism
- Delivery hose with inlet and outlet nozzles
- Torch bracket for wire feed on OSW / OSZ / TURN
- Interconnecting cables wire feed unit / controller

SPARE DELIVERY HOSE FOR ORBIFEED, complete, 4.5m

1.3.1706

SPARE DELIVERY HOSE FOR ORBIFEED, complete, without teflon hose, 4.5m

1.3.1719

SPARE DELIVERY HOSE TEFLON FOR ORBIFEED 4.7m

1.3.1712

SPARE WIRE INLET NOZZLE

1.3.1704

SPARE WIRE OUTLET NOOZLE (Wire ø 0.8 - 1.0mm)

1.3.1705

SPARE WIRE OUTLET NOOZLE (Wire ø 0.8mm)

1.3.1720

TORCH BRACKETS FOR WIRE FEED, complete

Can be fitted to TIG torch OSW / OSZ

TORCH BRACKET FOR WIRE FEED OSW 80-170 "STANDARD", OSZ INTERNAL

1.3.1708

TORCH BRACKET FOR WIRE FEED OSZ "STANDARD", OSW 80-170 INTERNAL

1.3.1709

TORCH BRACKET FOR WIRE FEED OSW 40

1.3.1710

SPARE TORCH BRACKET GFP OSW 80-170 "STANDARD", OSZ INTERNAL

1.0.1630

SPARE TORCH BRACKET GFP OSZ "STANDARD", OSW 80-170 INTERNAL

1.0.1638

SPARE TORCH BRACKET GFP OSW 40

1.0.1619

SPARE TORCH BRACKET ALU, OSW 80-170, OSZ

1.0.1634

SPARE TORCH BRACKET ALU, OSW 40

1.0.1639

