



ORBIFEED WIRE FEED UNITS

Compact and lightweight wire feed units in a Peli case for 5 kg or 15 kg standard spools.



ORBIFEED 5 WIRE FEED UNIT, for 5 kg spools

1.3.1701

ORBIFEED 15 WIRE FEED UNIT, for 15 kg spools

1.3.1702

Technical data:

Motor voltage / power
Weight
Dimensions (L x W x H)
Wire spools
Wire diameter

ORBIFEED 5

24 V DC, 6 W
approx. 7 kg
406 x 330 x 174 mm
Standard spools 5 kg
0.8 / 1.0 mm

ORBIFEED 15

24 V DC, 6 W
approx. 8 kg
525 x 436 x 217 mm
Standard spools 5 & 15 kg
0.8 / 1.0 mm

Package includes:

- Water-resistant and dust-proof Peli case
- Four-roller drive mechanism
- Delivery hose with inlet and outlet nozzles
- Spool adapter
- Wire feed unit / controller connection cable



SPARE DELIVERY HOSE FOR ORBIFEED, COMPLETE, 4.5 m

1.3.1706



SPARE WIRE FEED SPIRAL, RED, 4.5 m

1.3.1719



SPARE TEFLON WIRE CORE FOR ORBIFEED, 4.7 m

1.3.1712



SPARE WIRE INLET NOZZLE

1.3.1704



SPARE WIRE OUTLET NOZZLE (WIRE Ø 0.8 mm)

1.3.1720



SPARE WIRE OUTLET NOZZLE (WIRE Ø 1.0 mm)

1.3.1705

WIRE FEED CONSOLES,

cpl., can be mounted on TIG OSW torch



OSW 40 WIRE FEED CONSOLE

1.3.1710

'STANDARD' OSW 80 - 275 WIRE FEED CONSOLE

1.3.1708

OSW 80 - 275 WIRE FEED CONSOLE, INTERNAL

1.3.1709

OSW 80 - 275 WIRE FEED CONSOLE, COMFORT

1.3.1725

(3D adjustable through linear guide units)



SPARE OSW 40 GRP WIRE HOLDER

1.0.1619

SPARE OSW 80 - 275 GRP 'STANDARD' WIRE HOLDER

1.0.1630

SPARE OSW 80 - 275 GRP WIRE HOLDER, INTERNAL

1.0.1638



SPARE OSW 40 ALU WIRE HOLDER

1.0.1639



SPARE OSW 80 - 275 ALU WIRE HOLDER

1.0.1634